

# TECHNICAL DATA SHEET

## Product Name

DIY Windshield Repair Kit

**WJB Industrial Technologies, Inc.  
dba Automotive Parts Company**

Company address: 13660 Redwood Court,  
Chino ,CA91710, U.S.A.

Phone: (909) 465-5600

Fax: (909) 465-5199

Website: [www.WorkTechGlue.com](http://www.WorkTechGlue.com)

## PRODUCT DESCRIPTION

Visbella Windshield Repair Kit is very handy to help you to repair the broken windshield in just 20 minutes. This kit will minimize the appearance and stop the spread of chips and cracks in your windshield. It removes air from the break, fills it with durable resin and makes it even stronger than before. For best results, repairs should be made as soon as possible after the damage occurs and before the break is contaminated by dirt or water.

Kit Contains:

- (1) 1 x 2ml repair resin,
- (2) 3 x adhesive seal
- (3) 1 x pedestal,
- (4) 5 x curing film,
- (5) 1 x Instruction Manual
- (6) 1 x Razor Blade
- (7) 1 x injector with spring clip
- (8) 1 x cleaning cloth
- (9) 1 x Push pin
- (10) 2 x Black o-ring



## PHYSICAL PROPERTIES

Color: Clear

Odor: Acrylic

Vapor pressure: < 6 mm Hg (27 °C (80.6 °F))

Boiling point/range: > 149 °C (> 300.2 °F)

Density: 1.04

Flash point: 65 °C (149°F)

## PRODUCT BENEFITS

- Easy to use for all types of laminated windshields
- Minimizes the appearance of chips and cracks in your Windshield
- No heating is required
- Durable resin formula
- Good for multiple repairs
- Single ingredient - eliminates mixing
- No special tools required
- Quick repair within 30 minutes

## DIRECTIONS FOR USE

- (1).Clean damaged Area
- (2).Mount seal to Windshield
- (3).Mount pedestal to Adhesive Seal
- (4).Place resin into Pedestal
- (5).Connect injector to Pedestal and lock Plunger in Vacuum Position
- (6).Fill Injector with Air and move Plunger to Pressure
- (7).Remove Pedestal & adhesive seal from Glass
- (8).Apply resin in break area and cover with curing film
- (9).Curing & Finishing

## NOTE

- A. Avoid using in direct sunlight - work in a shaded area.
- B. Do not work on a hot windshield,park vehicle in shaded area and open windows to cool glass surface.
- C. A safety razor is required to remove components and finish repair.

**CAUTION:** Avoid any contact with eyes,skin and the body of the vehicle.

**KEEP OUT OF REACH OF CHILDREN**

## STORAGE

Products shall be ideally stored in a cool, dry location in un-opened containers at a temperature between 5 to 45 degree c.